




TWIN CORD-END TERMINALS (DIN 46228/4)

1. TEMPERATURE RANGE : -40°C UP TO + 105°C
2. TERMINAL MATERIAL : COPPER TUBE
3. PLATING : ELECTRO TIN PLATED
4. INSULATION MATERIAL : NYLON



WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)				COLOR SYSTEM			PACKING PCS
		F	L	C	W	FRENCH	GERMAN	DIN	
22 AWG 2x0.5 mm ²	CT205008	.315 (8.0)	.591 (15.0)	.059 (1.5)	.185 (4.7)				500 PCS
20 AWG 2x0.75 mm ²	CT207508	.315 (8.0)	.591 (15.0)	.071 (1.8)	.197 (5.0)				
	CT207510	.394 (10.0)	.669 (17.0)			BLUE	WHITE	GREY	
18 AWG 2x1.0 mm ²	CT210008	.315 (8.0)	.591 (15.0)	.081 (2.05)	.213 (5.4)				
	CT210010	.394 (10.0)	.669 (17.0)			RED	YELLOW	RED	
16 AWG 2x1.5 mm ²	CT215008	.315 (8.0)	.630 (16.0)	.087 (2.2)	.260 (6.6)				
	CT215012	.472 (12.0)	.787 (20.0)			BLACK	RED	BLACK	
14 AWG 2x2.5 mm ²	CT225010	.394 (10.0)	.728 (18.5)	.110 (2.8)	.307 (7.8)				
	CT225013	.512 (13.0)	.846 (21.5)			GREY	BLUE	BLUE	
12 AWG 2x4.0 mm ²	CT240012	.472 (12.0)	.906 (23.0)	.146 (3.7)	.346 (8.8)				
10 AWG 2x6.0 mm ²	CT260014	.551 (14.0)	1.024 (26.0)	.189 (4.8)	.394 (10.0)				
8 AWG 2x10.0 mm ²	CT210014	.551 (14.0)	1.024 (26.0)	.252 (6.4)	.512 (13)				
6 AWG 2x16.0 mm ²	CT216014	.551 (14.0)	1.181 (30.0)	.327 (8.3)	.724 (18.4)				

CORD END TERMINALS

