


NON-INSULATED CORD-END TERMINALS (DIN 46228/1)

1. TERMINAL MATERIAL : COPPER TUBE
2. PLATING : ELECTRO TIN PLATED



WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)			PACKING PCS
		L	C	W	
22 AWG 0.5 mm ²	CN005006	.236 (6.0)	.039 (1.0)	.075 (1.9)	1000 PCS
	CN005008	.315 (8.0)			
	CN005010	.394 (10.0)			
20 AWG 0.75 mm ²	CN007506	.236 (6.0)	.047 (1.2)	.087 (2.2)	
	CN007508	.315 (8.0)			
	CN007510	.394 (10.0)			
18 AWG 1.0 mm ²	CN010006	.236 (6.0)	.055 (1.4)	.094 (2.4)	
	CN010008	.315 (8.0)			
	CN010010	.394 (10.0)			
	CN010012	.472 (12.0)			
6 AWG 1.5 mm ²	CN015007	.276 (7.0)	.067 (1.7)	.110 (2.8)	
	CN015008	.315 (8.0)			
	CN015010	.394 (10.0)			
	CN015012	.472 (12.0)			
14 AWG 2.5 mm ²	CN025007	.276 (7.0)	.091 (2.3)	.134 (3.4)	
	CN025008	.315 (8.0)			
	CN025010	.394 (10.0)			
	CN025012	.472 (12.0)			
12 AWG 4.0 mm ²	CN040008	.315 (8.0)	.110 (2.8)	.157 (4.0)	
	CN040009	.354 (9.0)			
	CN040010	.394 (10.0)			
	CN040012	.472 (12.0)			
	CN040015	.591 (15.0)			
	CN040018	.709 (18.0)			
10 AWG 6.0 mm ²	CN060010	.394 (10.0)	.138 (3.5)	.185 (4.7)	
	CN060012	.472 (12.0)			
	CN060015	.591 (15.0)			
	CN060018	.709 (18.0)			
8 AWG 10 mm ²	CN100012	.472 (12.0)	.177 (4.5)	.228 (5.8)	
	CN100015	.591 (15.0)			
	CN100018	.709 (18.0)			
6 AWG 16 mm ²	CN160012	.472 (12.0)	.228 (5.8)	.295 (7.5)	
	CN160015	.591 (15.0)			
	CN160018	.709 (18.0)			
4 AWG 25 mm ²	CN250015	.591 (15.0)	.287 (7.3)	.374 (9.5)	
	CN250016	.630 (16.0)			
	CN250018	.709 (18.0)			
	CN250022	.866 (22.0)			
2 AWG 35 mm ²	CN350016	.630 (16.0)	.327 (8.3)	.413 (10.5)	
	CN350018	.709 (18.0)			
	CN350020	.787 (20.0)			
	CN350025	.984 (25.0)			
1/0 AWG 50 mm ²	CN500018	.709 (18.0)	.406 (10.3)	.512 (13.0)	
	CN500020	.787 (20.0)			
	CN500025	.984 (25.0)			
2/0 AWG 70 mm ²	CN700022	.866 (22.0)	.531 (13.5)	.610 (15.5)	
	CN700025	.984 (25.0)			
	CN700032	1.260 (32.0)			
3/0 AWG 95 mm ²	CN950025	.984 (25.0)	.579 (14.7)	.669 (17.0)	
	CN950032	1.260 (32.0)			
4/0 AWG 120 mm ²	CN120030	1.181 (30.0)	.657 (16.7)	.748 (19.0)	
	CN120032	1.260 (32.0)			
	CN120034	1.339 (34.0)			
250/300 MCM 150 mm ²	CN150032	1.260 (32.0)	.768 (19.5)	.846 (21.5)	
	CN150038	1.496 (38.0)			