


HEAT SHRINKABLE BUTT CONNECTORS


1. MAXIMUM ELECTRICAL RATING : 600 VOLTS
2. SHRINK TEMP : 150 °C
OPERATING TEMP : - 10°C ~ 105 °C
3. TERMINAL MATERIAL : COPPER TUBE
4. PLATING : ELECTRO TIN PLATED
5. INSULATION MATERIAL : HEAT SHRINKABLE TUBE



WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)				
		F	L	D	d	t
26~22 AWG 0.1~0.5 mm ²	BCT0.5H	.472 (12.0)	.945 (24.0)	.118 (3.0)	.039 (1.0)	0.16 (0.4)
22~16 AWG 0.5~1.5 mm ²	BCT1H	.591 (15.0)	1.457 (37.0)	.177 (4.5)	.063 (1.6)	.029 (0.75)
16~14 AWG 1.5~2.5 mm ²	BCT2H			.217 (5.5)	.091 (2.3)	.030 (0.8)
12~10 AWG 4~6 mm ²	BCT5H		1.614 (41.0)	.256 (6.5)	.142 (3.6)	.035 (0.9)

HEAT SHRINKABLE 3 WAY RING TERMINALS


1. MAXIMUM ELECTRICAL RATING : 600 VOLTS
2. SHRINK TEMP : 150 °C
OPERATING TEMP : - 10°C ~ 105 °C
3. TERMINAL MATERIAL : COPPER
4. BRAZED SEAM
5. PLATING : ELECTRO TIN PLATED
6. INSULATION MATERIAL : HEAT SHRINKABLE TUBE



WIRE RANGE AWG / mm ²	ITEM NO.	STUD SIZE d2	DIMENSIONS inch (mm)				
			F	E	D	d1	t
22~16 AWG 0.5~1.5 mm ²	3W1BH	#8 (4.3)	.315 (8.0)	.728 (18.5)	.177 (4.5)	.067 (1.7)	.030 (0.75)
16~14 AWG 1.5~2.5 mm ²	3W2BH		.354 (9.0)	.807 (20.5)	.217 (5.5)	.091 (2.3)	.031 (0.8)
12~10 AWG 4~6 mm ²	3W5BH		.413 (10.5)	.925 (23.5)	.256 (6.5)	.134 (3.4)	.039 (1.0)

HEAT SHRINKABLE 4 WAY RING TERMINALS

1. MAXIMUM ELECTRICAL RATING : 600 VOLTS
2. SHRINK TEMP : 150 °C
OPERATING TEMP : - 10°C ~ 105 °C
3. TERMINAL MATERIAL : COPPER
4. BRAZED SEAM
5. PLATING : ELECTRO TIN PLATED
6. INSULATION MATERIAL : HEAT SHRINKABLE TUBE



WIRE RANGE AWG / mm ²	ITEM NO.	STUD SIZE d2	DIMENSIONS inch (mm)				
			F	E	D	d1	t
22~16 AWG 0.5~1.5 mm ²	4W1BH	#8 (4.3)	.315 (8.0)	.728 (18.5)	.177 (4.5)	.067 (1.7)	.030 (0.75)
16~14 AWG 1.5~2.5 mm ²	4W2BH		.354 (9.0)	.807 (20.5)	.217 (5.5)	.091 (2.3)	.031 (0.8)
12~10 AWG 4~6 mm ²	4W5BH		.413 (10.5)	.925 (23.5)	.256 (6.5)	.134 (3.4)	.039 (1.0)