


DIN STANDARD
NON-INSULATED RING TERMINALS (DIN46234)

1. TERMINAL MATERIAL : COPPER
2. BRAZED SEAM
3. PLATING : ELECTRO TIN PLATED



WIRE RANGE AWG / mm ²	ITEM NO.	UL	STUD SIZE d2	DIMENSIONS inch (mm)						
				B	L	F	E	D	d1	t
2 A.W.G. 35 mm ²	DR6-35NB		1/4 (6.5)	.591 (15.0)	1.319 (33.5)	1.024 (26.0)	.472 (12.0)	.496 (12.6)	.354 (9.0)	.063 (1.6)
	DR8-35NB		5/16 (8.4)	.630 (16.0)	1.339 (34.0)	1.024 (26.0)				
	DR10-35NB		3/8 (10.5)	.709 (18.0)	1.417 (36.0)	1.063 (27.0)				
	DR12-35NB		1/2 (13.0)	.866 (22.0)	1.654 (42.0)	1.220 (31.0)				
	DR16-35NB		5/8 (17.0)	1.102 (28.0)	1.969 (50.0)	1.417 (36.0)				
1/0 A.W.G. 50 mm ²	DR6-50NB		1/4 (6.5)	.709 (18.0)	1.693 (43.0)	1.339 (34.0)	.630 (16.0)	.591 (15.0)	.433 (11.0)	.071 (1.8)
	DR8-50NB		5/16 (8.4)	.709 (18.0)	1.693 (43.0)	1.339 (34.0)				
	DR10-50NB		3/8 (10.5)	.709 (18.0)	1.693 (43.0)	1.339 (34.0)				
	DR12-50NB		1/2 (13.0)	.866 (22.0)	1.850 (47.0)	1.417 (36.0)				
	DR16-50NB		5/8 (17.0)	1.102 (28.0)	2.126 (54.0)	1.575 (40.0)				
2/0 A.W.G. 70 mm ²	DR6-70NB		1/4 (6.5)	.866 (22.0)	1.929 (49.0)	1.496 (38.0)	.709 (18.0)	.689 (17.5)	.512 (13.0)	.079 (2.0)
	DR8-70NB		5/16 (8.4)	.866 (22.0)	1.929 (49.0)	1.496 (38.0)				
	DR10-70NB		3/8 (10.5)	.866 (22.0)	1.929 (49.0)	1.496 (38.0)				
	DR12-70NB		1/2 (13.0)	.866 (22.0)	1.929 (49.0)	1.496 (38.0)				
	DR16-70NB		5/8 (17.0)	1.102 (28.0)	2.205 (56.0)	1.654 (42.0)				
3/0 A.W.G. 95 mm ²	DR8-95NB		5/16 (8.4)	.945 (24.0)	2.126 (54.0)	1.654 (42.0)	.787 (20.0)	.807 (20.5)	.591 (15.0)	.098 (2.5)
	DR10-95NB		3/8 (10.5)	.945 (24.0)	2.126 (54.0)	1.654 (42.0)				
	DR12-95NB		1/2 (13.0)	.945 (24.0)	2.126 (54.0)	1.654 (42.0)				
	DR16-95NB		5/8 (17.0)	1.102 (28.0)	2.283 (58.0)	1.732 (44.0)				
	DR8-120NB		5/16 (8.4)	.945 (24.0)	2.205 (56.0)	1.732 (44.0)				
4/0 A.W.G. 120 mm ²	DR10-120NB		3/8 (10.5)	.945 (24.0)	2.205 (56.0)	1.732 (44.0)	.866 (22.0)	.906 (23.0)	.650 (16.5)	.118 (3.0)
	DR12-120NB		1/2 (13.0)	.945 (24.0)	2.205 (56.0)	1.732 (44.0)				
	DR16-120NB		5/8 (17.0)	1.102 (28.0)	2.441 (62.0)	1.890 (48.0)				
	DR10-150NB		3/8 (10.5)	1.181 (30.0)	2.559 (65.0)	1.969 (50.0)	.945 (24.0)	1.024 (26.0)	.748 (19.0)	.126 (3.2)
250/300 MCM 150 mm ²	DR12-150NB		1/2 (13.0)	1.181 (30.0)	2.559 (65.0)	1.969 (50.0)				
	DR16-150NB		5/8 (17.0)	1.181 (30.0)	2.559 (65.0)	1.969 (50.0)				
	DR10-185NB		3/8 (10.5)	1.417 (36.0)	2.677 (68.0)	1.969 (50.0)	1.102 (28.0)	1.134 (28.8)	.827 (21.0)	.138 (3.5)
300/350 MCM 185 mm ²	DR12-185NB		1/2 (13.0)	1.417 (36.0)	2.677 (68.0)	1.969 (50.0)				
	DR16-185NB		5/8 (17.0)	1.417 (36.0)	2.677 (68.0)	1.969 (50.0)				
	DR10-240NB		3/8 (10.5)	1.496 (38.0)	2.953 (75.0)	2.205 (56.0)	1.260 (32.0)	1.272 (32.3)	.925 (23.5)	.157 (4.0)
400 MCM 240 mm ²	DR12-240NB		1/2 (13.0)	1.496 (38.0)	2.953 (75.0)	2.205 (56.0)				
	DR16-240NB		5/8 (17.0)	1.496 (38.0)	2.953 (75.0)	2.205 (56.0)				