


DOUBLE CRIMP DIN STANDARD PVC INSULATED RING TERMINALS ~~~EASY ENTRY SLEEVE~~~

1. MAXIMUM ELECTRICAL RATING : 600 VOLTS
2. MAXIMUM TEMPERATURE : 105°C
3. TERMINAL MATERIAL : COPPER
4. PLATING : ELECTRO TIN PLATED
5. REINFORCEMENT SLEEVE : C TYPE SLEEVE
6. INSULATION MATERIAL : VINYL (PVC)



3 pcs design



WIRE RANGE AWG / mm ²	ITEM NO.	UL	STUD SIZE d2	DIMENSIONS inch (mm)						
				B	L	F	E	D	d1	t
 22~16 AWG 0.5~1.5 mm ²	DR2.5-1VC		#3 (2.7)	.236 (6.0)	.748 (19.0)	.630 (16.0)	.394 (10.0)	.177 (4.5)	.063 (1.6)	.031 (0.8)
	DR3-1VC		#4 (3.2)	.236 (6.0)	.748 (19.0)	.630 (16.0)				
	DR3.5-1VC		#6 (3.7)	.236 (6.0)	.748 (19.0)	.630 (16.0)				
	DR4-1VC		#8 (4.3)	.315 (8.0)	.827 (21.0)	.669 (17.0)				
	DR5-1VC		#10 (5.3)	.394 (10.0)	.906 (23.0)	.709 (18.0)				
	DR6-1VC		1/4 (6.5)	.433 (11.0)	1.004 (25.5)	.787 (20.0)				
	DR8-1VC		5/16 (8.4)	.551 (14.0)	1.102 (28.0)	.827 (21.0)				
 16~14 AWG 1.5~2.5 mm ²	DR10-1VC		3/8 (10.5)	.709 (18.0)	1.260 (32.0)	.906 (23.0)	.394 (10.0)	.197 (5.0)	.091 (2.3)	.031 (0.8)
	DR3-2VC		#4 (3.2)	.236 (6.0)	.748 (19.0)	.630 (16.0)				
	DR3.5-2VC		#6 (3.7)	.236 (6.0)	.748 (19.0)	.630 (16.0)				
	DR4-2VC		#8 (4.3)	.315 (8.0)	.827 (21.0)	.669 (17.0)				
	DR5-2VC		#10 (5.3)	.394 (10.0)	.945 (24.0)	.748 (19.0)				
	DR6-2VC		1/4 (6.5)	.433 (11.0)	1.043 (26.5)	.827 (21.0)				
	DR8-2VC		5/16 (8.4)	.551 (14.0)	1.142 (29.0)	.866 (22.0)				
 12~10 AWG 4~6 mm ²	DR10-2VC		3/8 (10.5)	.709 (18.0)	1.260 (32.0)	.906 (23.0)	.512 (13.0)	.268 (6.8)	.142 (3.6)	.039 (1.0)
	DR4-6VC		#8 (4.3)	.315 (8.0)	.984 (25.0)	.827 (21.0)				
	DR5-6VC		#10 (5.3)	.394 (10.0)	1.063 (27.0)	.866 (22.0)				
	DR6-6VC		1/4 (6.5)	.433 (11.0)	1.122 (28.5)	.906 (23.0)				
	DR8-6VC		5/16 (8.4)	.551 (14.0)	1.299 (33.0)	1.024 (26.0)				
	DR10-6VC		3/8 (10.5)	.709 (18.0)	1.457 (37.0)	1.102 (28.0)				
	DR12-6VC		1/2 (13.0)	.748 (19.0)	1.693 (43.0)	1.319 (33.5)				

DIN STANDARD NYLON-INSULATED RING TERMINALS (DIN 46237)

1. MAXIMUM ELECTRICAL RATING : 600 VOLTS
2. MAXIMUM TEMPERATURE : 105°C
3. TERMINAL MATERIAL : COPPER
4. BRAZED SEAM
5. PLATING
6. INSULATION MATERIAL : EASY ENTRY NYLON



2 pcs design



WIRE RANGE AWG / mm ²	ITEM NO.	STUD SIZE d2	DIMENSIONS inch (mm)						
			B	L	F	E	D	d1	t
 8 A.W.G. 10 mm ²	DR5-10BA	#10 (5.3)	.394 (10.0)	1.142 (29.0)	.945 (24.0)	.630 (16.0)	.315 (8.0)	.177 (4.5)	.043 (1.1)
	DR6-10BA	1/4 (6.5)	.433 (11.0)	1.201 (30.5)	.984 (25.0)				
	DR8-10BA	5/16 (8.4)	.551 (14.0)	1.398 (35.5)	1.102 (28.0)				
	DR10-10BA	3/8 (10.5)	.709 (18.0)	1.496 (38.0)	1.142 (29.0)				
	DR12-10BA	1/2 (13.0)	.866 (22.0)	1.654 (42.0)	1.220 (31.0)				
 6 A.W.G. 16 mm ²	DR5-16BA	#10 (5.3)	.433 (11.0)	1.457 (37.0)	1.240 (31.5)	.846 (21.5)	.433 (11.0)	.228 (5.8)	.047 (1.2)
	DR6-16BA	1/4 (6.5)	.433 (11.0)	1.457 (37.0)	1.240 (31.5)				
	DR8-16BA	5/16 (8.4)	.551 (14.0)	1.594 (40.5)	1.319 (33.5)				
	DR10-16BA	3/8 (10.5)	.709 (18.0)	1.752 (44.5)	1.398 (35.5)				
	DR12-16BA	1/2 (13.0)	.866 (22.0)	1.909 (48.5)	1.476 (37.5)				
 4 A.W.G. 25 mm ²	DR5-25BA	#10 (5.3)	.472 (12.0)	1.732 (44.0)	1.496 (38.0)	.945 (24.0)	.512 (13.0)	.295 (7.5)	.059 (1.5)
	DR6-25BA	1/4 (6.5)	.472 (12.0)	1.732 (44.0)	1.496 (38.0)				
	DR8-25BA	5/16 (8.4)	.630 (16.0)	1.811 (46.0)	1.496 (38.0)				
	DR10-25BA	3/8 (10.5)	.709 (18.0)	1.890 (48.0)	1.535 (39.0)				
	DR12-25BA	1/2 (13.0)	.866 (22.0)	2.165 (55.0)	1.732 (44.0)				
 2 A.W.G. 35 mm ²	DR16-25BA	5/8 (17.0)	1.102 (28.0)	2.441 (62.0)	1.890 (48.0)	1.063 (27.0)	.571 (14.5)	.354 (9.0)	.063 (1.6)
	DR6-35BA	1/4 (6.5)	.591 (15.0)	1.909 (48.5)	1.614 (41.0)				
	DR8-35BA	5/16 (8.4)	.630 (16.0)	1.929 (49.0)	1.614 (41.0)				
	DR10-35BA	3/8 (10.5)	.709 (18.0)	2.008 (51.0)	1.654 (42.0)				
	DR12-35BA	1/2 (13.0)	.866 (22.0)	2.244 (57.0)	1.811 (46.0)				
	DR16-35BA	5/8 (17.0)	1.102 (28.0)	2.559 (65.0)	2.008 (51.0)				