





PVC FULLY INSULATED RECEPTACLE DISCONNECTS


1. MAXIMUM ELECTRICAL RATING : 300 VOLTS
2. MAXIMUM TEMPERATURE : 75°C
3. TERMINAL MATERIAL : BRASS
4. PLATING : ELECTRO TIN PLATED
5. INSULATION MATERIAL : VINYL (PVC)










WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)							
		B	F	L	E	D	d1	t	
 22~16 AWG 0.5~1.5 mm ²	RE1-4VF	.157 (4.0)	.354 (9.0)	.866 (22.0)	.433 (11.0)	.157 (4.0)	.067 (1.7)	.016 (0.4)	
	RE1-4.5VF	.177 (4.5)							
 16~14 AWG 1.5~2.5 mm ²	RE2-4VF	.157 (4.0)		.906 (23.0)		.925 (23.5)	.217 (5.5)	.091 (2.3)	.016 (0.4)
	RE2-4.5VF	.177 (4.5)							
	RE2-5VF	.197 (5.0)							
 12~ 10 AWG 4~6 mm ²	RE5-5VF	.197 (5.0)		1.004 (25.5)		.492 (12.5)	.134 (3.4)	.016 (0.4)	

DOUBLE CRIMP PVC FULLY INSULATED RECEPTACLE DISCONNECTS


REINFORCEMENT SLEEVE : D TYPE SLEEVE










WIRE RANGE AWG / mm ²	ITEM NO.	UL	DIMENSIONS inch (mm)							
			B	F	L	E	D	d1	t	
 22~16 AWG 0.5~1.5 mm ²	RE1-4VFD		.157 (4.0)	.354 (9.0)	.886 (22.5)	.433 (11.0)	.161 (4.1)	.067 (1.7)	.016 (0.4)	
	RE1-4.5VFD		.177 (4.5)							
 16~14 AWG 1.5~2.5 mm ²	RE2-4VFD		.157 (4.0)		.925 (23.5)		.512 (13.0)	.256 (6.5)	.091 (2.3)	.016 (0.4)
	RE2-4.5VFD		.177 (4.5)							
	RE2-5VFD		.197 (5.0)							
 12~ 10 AWG 4~6 mm ²	RE5-5VFD		.197 (5.0)		.984 (25.0)		.134 (3.4)	.016 (0.4)		

DOUBLE CRIMP PVC FULLY INSULATED RECEPTACLE DISCONNECTS ~~~ EASY ENTRY SLEEVE ~~~

REINFORCEMENT SLEEVE : C TYPE SLEEVE



WIRE RANGE AWG / mm ²	ITEM NO.	UL	DIMENSIONS inch (mm)							
			B	F	L	E	D	d1	t	
 22~16 AWG 0.5~1.5 mm ²	RE1-4VFC		.157 (4.0)	.354 (9.0)	.886 (22.5)	.433 (11.0)	.169 (4.3)	.067 (1.7)	.016 (0.4)	
	RE1-4.5VFC		.177 (4.5)							
 16~14 AWG 1.5~2.5 mm ²	RE2-4VFC		.157 (4.0)		.925 (23.5)		.512 (13.0)	.256 (6.5)	.091 (2.3)	.016 (0.4)
	RE2-4.5VFC		.177 (4.5)							
	RE2-5VFC		.197 (5.0)							
 12~ 10 AWG 4~6 mm ²	RE5-5VFC		.197 (5.0)		.984 (25.0)		.134 (3.4)	.016 (0.4)		