


DOUBLE CRIMP PVC INSULATED FEMALE DISCONNECTS















~~~ EASY ENTRY SLEEVE ~~~

1. MAXIMUM ELECTRICAL RATING : 300 VOLTS
2. MAXIMUM TEMPERATURE : 75°C
3. TERMINAL MATERIAL : BRASS
4. PLATING : ELECTRO TIN PLATED
5. REINFORCEMENT SLEEVE : C TYPE SLEEVE
6. INSULATION MATERIAL : VINYL (PVC)



3 pcs design



| WIRE RANGE<br>AWG / mm <sup>2</sup>                                                                                         | ITEM NO.   | UL                                                                                  | DIMENSIONS inch (mm)   |            |             |              |             |            |            |             |
|-----------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------------------------------------------|------------------------|------------|-------------|--------------|-------------|------------|------------|-------------|
|                                                                                                                             |            |                                                                                     | NEMA TAB               | B          | F           | L            | E           | D          | d1         | t           |
| <br>22~16 AWG<br>0.5~1.5 mm <sup>2</sup>   | F1-2.8VC/5 |    | .020*.110<br>(0.5*2.8) | .126 (3.2) | .252 (6.4)  | .728 (18.5)  | .394 (10.0) | .169 (4.3) | .067 (1.7) | .010 (0.25) |
|                                                                                                                             | F1-2.8VC/8 |    | .032*.110<br>(0.8*2.8) |            |             |              |             |            |            | .010 (0.25) |
|                                                                                                                             | F1-4.8VC/5 |    | .020*.187<br>(0.5*4.8) | .197 (5.0) | .256 (6.5)  | .748 (19.0)  |             |            |            | .014 (0.35) |
|                                                                                                                             | F1-4.8VC/8 |   | .032*.187<br>(0.8*4.8) |            |             |              |             |            |            | .014 (0.35) |
|                                                                                                                             | F1-6.4VC   |  | .032*.250<br>(0.8*6.4) | .260 (6.6) | .311 (7.9)  | .827 (21.0)  |             |            |            | .016 (0.4)  |
|                                                                                                                             | F1-8VC     |                                                                                     | .032*.312<br>(0.8*8.0) | .331 (8.4) | .394 (10.0) | .945 (24.0)  |             |            |            | .016 (0.4)  |
| <br>16~14 AWG<br>1.5~2.5 mm <sup>2</sup> | F2-2.8VC/5 |  | .020*.110<br>(0.5*2.8) | .126 (3.2) | .252 (6.4)  | .728 (18.5)  | .394 (10.0) | .197 (5.0) | .091 (2.3) | .010 (0.25) |
|                                                                                                                             | F2-2.8VC/8 |  | .032*.110<br>(0.8*2.8) |            |             |              |             |            |            | .010 (0.25) |
|                                                                                                                             | F2-4.8VC/5 |  | .020*.187<br>(0.5*4.8) | .197 (5.0) | .256 (6.5)  | .748 (19.0)  |             |            |            | .014 (0.35) |
|                                                                                                                             | F2-4.8VC/8 |  | .032*.187<br>(0.8*4.8) |            |             |              |             |            |            | .014 (0.35) |
|                                                                                                                             | F2-6.4VC   |  | .032*.250<br>(0.8*6.4) | .260 (6.6) | .311 (7.9)  | .827 (21.0)  |             |            |            | .016 (0.4)  |
|                                                                                                                             | F2-8VC     |                                                                                     | .032*.312<br>(0.8*8.0) | .331 (8.4) | .394 (10.0) | .945 (24.0)  |             |            |            | .016 (0.4)  |
|                                                                                                                             | F2-9.5VC   |                                                                                     | .047*.375<br>(1.2*9.5) | .390 (9.9) | .492 (12.5) | 1.024 (26.0) |             |            |            | .020 (0.5)  |
| <br>12~10 AWG<br>4~6 mm <sup>2</sup>     | F5-6.4VC   |  | .032*.250<br>(0.8*6.4) | .260 (6.6) | .311 (7.9)  | .925 (23.5)  | .492 (12.5) | .256 (6.5) | .134 (3.4) | .016 (0.4)  |
|                                                                                                                             | F5-9.5VC   |                                                                                     | .047*.375<br>(1.2*9.5) | .390 (9.9) | .492 (12.5) | 1.122 (28.5) |             |            |            | .020 (0.5)  |