




PVC INSULATED BULLET DISCONNECTS

1. MAXIMUM ELECTRICAL RATING : 300 VOLTS
2. MAXIMUM TEMPERATURE : 75°C
3. TERMINAL MATERIAL : BRASS
4. PLATING : ELECTRO TIN PLATED
5. INSULATION MATERIAL : VINYL (PVC)



2 pcs design




WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)						
		B	F	L	E	D	d1	t
 22~16 AWG 0.5~1.5 mm ²	BD1-4V	.157 (4.0)	.335 (8.5)	.827 (21.0)	.394 (10.0)	.157 (4.0)	.067 (1.7)	.016 (0.4)
	BD1-4.5V	.177 (4.5)						
 16~14 AWG 1.5~2.5 mm ²	BD2-4V	.157 (4.0)						
	BD2-4.5V	.177 (4.5)						
	BD2-5V	.197 (5.0)						
 12~ 10 AWG 4~6 mm ²	BD5-5V	.197 (5.0)						








DOUBLE CRIMP PVC INSULATED BULLET DISCONNECTS

REINFORCEMENT SLEEVE : D TYPE SLEEVE



3 pcs design




WIRE RANGE AWG / mm ²	ITEM NO.	UL	DIMENSIONS inch (mm)						
			B	F	L	E	D	d1	t
 22~16 AWG 0.5~1.5 mm ²	BD1-4VD		.157 (4.0)	.335 (8.5)	.827 (21.0)	.394 (10.0)	.161 (4.1)	.067 (1.7)	.016 (0.4)
	BD1-4.5VD		.177 (4.5)						
 16~14 AWG 1.5~2.5 mm ²	BD2-4VD		.157 (4.0)						
	BD2-4.5VD		.177 (4.5)						
	BD2-5VD		.197 (5.0)						
 12~ 10 AWG 4~6 mm ²	BD5-5VD		.197 (5.0)						








DOUBLE CRIMP PVC INSULATED BULLET DISCONNECTS ~~~ EASY ENTRY SLEEVE ~~~

REINFORCEMENT SLEEVE : C TYPE SLEEVE



3 pcs design



WIRE RANGE AWG / mm ²	ITEM NO.	UL	DIMENSIONS inch (mm)						
			B	F	L	E	D	d1	t
 22~16 AWG 0.5~1.5 mm ²	BD1-4VC		.157 (4.0)	.335 (8.5)	.827 (21.0)	.394 (10.0)	.169 (4.3)	.067 (1.7)	.016 (0.4)
	BD1-4.5VC		.177 (4.5)						
 16~14 AWG 1.5~2.5 mm ²	BD2-4VC		.157 (4.0)						
	BD2-4.5VC		.177 (4.5)						
	BD2-5VC		.197 (5.0)						
 12~ 10 AWG 4~6 mm ²	BD5-5VC		.197 (5.0)						