





SERIE 416.18 / SERIES 416.18

| Series 416.18 | Omologazioni / Approvals | | | | | |
|------------------|--|--------------------------------------|-------------|--|-------------|--------------------------------------|
| | EN 60252-1/A1   Tensione / Voltage: 250 V ~ 10000 h cl. B 25/85/21 400 V ~ 3000 h cl. C 25/85/21 425 V ~ 1000 h cl. D 25/85/21 | | | Classe di sicurezza / Safety protection class: S0 Valori omologati / Approved range: 1 ÷ 70 µF 1 ÷ 25 µF 1 ÷ 25 µF | | |
| C(µF) | DxH (mm) | Codice / Part number 416.18.XX.KK | DxH (mm) | Codice / Part number 416.18.XX.KK | DxH (mm) | Codice / Part number 416.18.XX.KK |
| 1 | 25x50 | 416.18.01.KK | | | | |
| 1,5 | 25x50 | 416.18.02.KK | 28x55 | 416.18.44.KK | | |
| 2 | 25x50 | 416.18.03.KK | 28x55 | 416.18.45.KK | | |
| 2,5 | 25x50 | 416.18.04.KK | 28x55 | 416.18.46.KK | | |
| 3 | 25x50 | 416.18.05.KK | 28x55 | 416.18.47.KK | 22x73 | 416.18.A7.KK |
| 3,15 | 25x50 | 416.18.06.KK | 28x55 | 416.18.48.KK | | |
| 3,5 | 25x50 | 416.18.07.KK | 28x55 | 416.18.49.KK | 36x58 | 416.18.B8.KK |
| 4 | 25x50 | 416.18.08.KK | 28x55 | 416.18.50.KK | | |
| 4,5 | 25x50 | 416.18.09.KK | 28x55 | 416.18.51.KK | | |
| 5 | 25x55 | 416.18.10.KK | 28x55 | 416.18.52.KK | 20x60 | 416.18.92.KK |
| 6 | 25x55 | 416.18.11.KK | 28x55 | 416.18.53.KK | 30x55 | 416.18.69.KK |
| 6,3 | 30x55 | 416.18.12.KK | 28x55 | 416.18.54.KK | | |
| 7 | 30x55 | 416.18.13.KK | 28x55 | 416.18.55.KK | 36x58 | 416.18.D2.KK |
| 7,5 | 30x55 | 416.18.14.KK | 28x55 | 416.18.56.KK | | |
| 8 | 30x55 | 416.18.15.KK | 28x55 | 416.18.57.KK | 36x58 | 416.18.D3.KK |
| 9 | 30x55 | 416.18.16.KK | 32x55 | 416.18.58.KK | 36x58 | 416.18.D4.KK |
| 10 | 30x55 | 416.18.17.KK | 32x55 | 416.18.59.KK | | |
| 11 | 30x55 | 416.18.18.KK | 32x55 | 416.18.60.KK | 35x55 | 416.18.B1.KK |
| 12 | 36x58 | 416.18.19.KK | 32x55 | 416.18.61.KK | 30x70 | 416.18.91.KK |
| 12,5 | 36x58 | 416.18.20.KK | 30x70 | 416.18.B6.KK | 32x55 | 416.18.B5.KK |
| 13 | 36x58 | 416.18.21.KK | | | | |
| 13,5 | 36x58 | 416.18.22.KK | | | | |
| 14 | 36x58 | 416.18.23.KK | 30x70 | 416.18.79.KK | | |
| 15 | 36x58 | 416.18.24.KK | 30x70 | 416.18.A9.KK | | |
| 16 | 36x58 | 416.18.25.KK | 30x92 | 416.18.83.KK | 30x70 | 416.18.E3.KK |
| 17,5 | 36x70 | 416.18.26.KK | | | | |
| 18 | 36x70 | 416.18.27.KK | 35x70 | 416.18.D7.KK | | |
| 20 | 36x70 | 416.18.28.KK | 30x92 | 416.18.B7.KK | 35x68 | 416.18.A5.KK |
| 22 | 36x70 | 416.18.29.KK | | | | |
| 25 | 40x70 | 416.18.30.KK | 35x92 | 416.18.A8.KK | 36x70 | 416.18.E2.KK |
| 30 | 40x70 | 416.18.31.KK | | | | |
| 31,5 | 40x92 | 416.18.32.KK | 40x70 | 416.18.A6.KK | | |
| 35 | 40x92 | 416.18.33.KK | 35x92 | 416.18.84.KK | 45x70 | 416.18.66.KK |
| 40 | 40x92 | 416.18.34.KK | 45x70 | 416.18.D8.KK | | |
| 45 | 40x92 | 416.18.35.KK | | | | |
| 50 | 45x92 | 416.18.36.KK | | | | |
| 55 | 45x92 | 416.18.37.KK | | | | |
| 60 | 45x92 | 416.18.70.KK | 45x117 | 416.18.38.KK | | |
| 70 | 45x117 | 416.18.39.KK | 50x92 | 416.18.82.KK | | |
| 80 | 45x117 | 416.18.40.KK | | | | |
| 90 | 50x117 | 416.18.41.KK | | | | |
| 100 | 50x117 | 416.18.42.KK | | | | |



UL recognition
File E192559
250V~

Disponibile su richiesta
Available on request

Valori omologati
Approved range
1-100µF

Altre dimensioni a richiesta
Other sizes available upon request

SERIE 416.10 / SERIES 416.10

| Series 416.10 | Omologazioni / Approvals | | | | | |
|------------------|--|--------------------------------------|----------|---|----------|--------------------------------------|
| | EN 60252-1/A1 Tensione / Voltage: 400 V ~ 10000 h cl. B 25/85/21 425 V ~ 10000 h cl. B 25/85/21 450 V ~ 3000 h cl. C 25/85/21 475 V ~ 3000 h cl. C 25/85/21 | | | Classe di sicurezza / Safety protection class: S0 Valori omologati / Approved range: 45 ÷ 60 µF 2 ÷ 40 µF 45 ÷ 60 µF 2 ÷ 40 µF | | |
| C(µF) | DxH (mm) | Codice / Part number 416.10.XX.KK | DxH (mm) | Codice / Part number 416.10.XX.KK | DxH (mm) | Codice / Part number 416.10.XX.KK |
| 2 | 25x49 | 416.10.31.KK | 28x55 | 416.10.01.KK | 30x56 | 416.10.73.KK |
| 2,5 | 25x49 | 416.10.32.KK | 28x55 | 416.10.02.KK | 20x60 | 416.10.B5.KK |
| 3 | 25x49 | 416.10.33.KK | 28x55 | 416.10.03.KK | 30x56 | 416.10.74.KK |
| 3,15 | 25x49 | 416.10.34.KK | 28x55 | 416.10.04.KK | | |
| 3,5 | 25x55 | 416.10.35.KK | 28x55 | 416.10.05.KK | 25x49 | 416.10.C1.KK |
| 4 | 25x55 | 416.10.37.KK | 28x55 | 416.10.06.KK | 30x56 | 416.10.38.KK |
| 4,5 | 25x55 | 416.10.C8.KK | 28x55 | 416.10.07.KK | 30x56 | 416.10.39.KK |
| 5 | 30x56 | 416.10.76.KK | 28x55 | 416.10.08.KK | 32x55 | 416.10.B2.KK |
| 5,5 | 30x56 | 416.10.41.KK | 32x55 | 416.10.79.KK | | |
| 6 | 30x56 | 416.10.82.KK | 32x55 | 416.10.09.KK | 30x50 | 416.10.B7.KK |
| 6,3 | 30x56 | 416.10.83.KK | 32x55 | 416.10.10.KK | | |
| 7 | 30x56 | 416.10.85.KK | 32x55 | 416.10.12.KK | 30x50 | 416.10.D9.KK |
| 7,5 | 36x58 | 416.10.44.KK | 32x55 | 416.10.89.KK | 30x50 | 416.10.B8.KK |
| 8 | 36x58 | 416.10.81.KK | 32x55 | 416.10.13.KK | 30x70 | 416.10.52.KK |
| 9 | 36x58 | 416.10.14.KK | 30x70 | 416.10.36.KK | | |
| 10 | 36x58 | 416.10.15.KK | 30x70 | 416.10.47.KK | 27x88 | 416.10.B4.KK |
| 11 | 36x58 | 416.10.16.KK | | | | |
| 12 | 36x70 | 416.10.17.KK | | | | |
| 12,5 | 36x70 | 416.10.18.KK | 36x58 | 416.10.H2.KK | | |
| 13 | 36x70 | 416.10.19.KK | | | | |
| 14 | 36x70 | 416.10.21.KK | 40x70 | 416.10.49.KK | 35x68 | 416.10.D6.KK |
| 15 | 36x70 | 416.10.22.KK | 30x92 | 416.10.46.KK | 45x70 | 416.10.F2.KK |
| 16 | 36x70 | 416.10.99.KK | 40x70 | 416.10.23.KK | 45x70 | 416.10.A2.KK |
| 18 | 40x70 | 416.10.24.KK | 45x70 | 416.10.A3.KK | 36x70 | 416.10.E3.KK |
| 20 | 40x70 | 416.10.25.KK | 45x92 | 416.10.F5.KK | | |
| 22 | 40x92 | 416.10.68.KK | 40x70 | 416.10.55.KK | | |
| 25 | 40x92 | 416.10.26.KK | 45x70 | 416.10.97.KK | 35x92 | 416.10.H1.KK |
| 30 | 40x92 | 416.10.70.KK | 45x70 | 416.10.B9.KK | 45x92 | 416.10.G8.KK |
| 31,5 | 45x92 | 416.10.27.KK | 40x92 | 416.10.A9.KK | | |
| 32 | 45x92 | 416.10.72.KK | 40x92 | 416.10.H3.KK | | |
| 35 | 45x92 | 416.10.28.KK | | | | |
| 36 | 45x92 | 416.10.65.KK | | | | |
| 40 | 45x92 | 416.10.29.KK | 50x92 | 416.10.G4.KK | 40x117 | 416.10.A8.KK |
| 45 | 45x117 | 416.10.63.KK | 50x92 | 416.10.90.KK | | |
| 50 | 45x117 | 416.10.30.KK | 50x92 | 416.10.62.KK | | |
| 55 | 45x117 | 416.10.64.KK | 50x92 | 416.10.86.KK | | |
| 60 | 50x117 | 416.10.61.KK | 55x92 | 416.10.57.KK | | |
| 70 | 50x117 | 416.10.67.KK | | | | |
| 80 | 55x120 | 416.10.87.KK | | | | |



UL recognition
File E192559
330V~ / 450V~



Disponibile su richiesta
Available on request

Valori omologati
Approved range
1-100µF

Altre dimensioni a richiesta
Other sizes available upon request



SERIE 416.17 / SERIES 416.17

| Series 416.17 | Omologazioni / Approvals | | | | | |
|------------------|---|--------------------------------------|----------|---|----------|--------------------------------------|
| | EN 60252-1/A1   | | | Classe di sicurezza / Safety protection class: S0 | | |
| | Tensione / Voltage: 425 V ~ 30000 h cl. A 25/85/21 475 V ~ 10000 h cl. B 25/85/21 500 V ~ 3000 h cl. C 25/85/21 | | | Valori omologati / Approved range: 1 ÷ 45 µF 1 ÷ 70 µF 1 ÷ 25 µF | | |
| C(µF) | DxH (mm) | Codice / Part number 416.17.XX.KK | DxH (mm) | Codice / Part number 416.17.XX.KK | DxH (mm) | Codice / Part number 416.17.XX.KK |
| 1 | 25x49 | 416.17.71.KK | 28x55 | 416.17.01.KK | 25x55 | 416.17.E3.KK |
| 1,5 | 25x49 | 416.17.73.KK | 28x55 | 416.17.23.KK | 25x55 | 416.17.E4.KK |
| 2 | 25x49 | 416.17.74.KK | 28x55 | 416.17.02.KK | 25x55 | 416.17.D2.KK |
| 2,5 | 25x55 | 416.17.75.KK | 28x55 | 416.17.03.KK | 30x50 | 416.17.F8.KK |
| 3 | 25x55 | 416.17.77.KK | 28x55 | 416.17.04.KK | 30x50 | 416.17.G4.KK |
| 3,15 | 25x55 | 416.17.C2.KK | 28x55 | 416.17.05.KK | 30x50 | 416.17.F9.KK |
| 3,5 | 25x55 | 416.17.C3.KK | 28x55 | 416.17.06.KK | 30x50 | 416.17.G2.KK |
| 4 | 30x56 | 416.17.81.KK | 28x55 | 416.17.07.KK | 30x50 | 416.17.G3.KK |
| 4,5 | 30x56 | 416.17.82.KK | 32x55 | 416.17.76.KK | 30x50 | 416.17.E7.KK |
| 5 | 30x56 | 416.17.83.KK | 32x55 | 416.17.08.KK | 30x50 | 416.17.C6.KK |
| 6 | 36x58 | 416.17.99.KK | 32x55 | 416.17.09.KK | 30x56 | 416.17.44.KK |
| 6,3 | 36x58 | 416.17.93.KK | 32x55 | 416.17.10.KK | 30x70 | 416.17.F3.KK |
| 7 | 36x58 | 416.17.11.KK | 30x70 | 416.17.F4.KK | | |
| 7,5 | 36x58 | 416.17.97.KK | | | | |
| 8 | 36x58 | 416.17.12.KK | 30x70 | 416.17.B5.KK | 30x92 | 416.17.E5.KK |
| 9 | 36x70 | 416.17.24.KK | | | | |
| 10 | 36x70 | 416.17.13.KK | | | | |
| 12 | 40x70 | 416.17.29.KK | 36x70 | 416.17.14.KK | | |
| 12,5 | 40x70 | 416.17.30.KK | | | | |
| 14 | 40x70 | 416.17.15.KK | | | | |
| 15 | 40x70 | 416.17.26.KK | | | | |
| 16 | 40x92 | 416.17.54.KK | 45x70 | 416.17.50.KK | 40x70 | 416.17.16.KK |
| 17,5 | 40x92 | 416.17.59.KK | | | | |
| 18 | 40x92 | 416.17.17.KK | 45x70 | 416.17.D3.KK | | |
| 20 | 40x92 | 416.17.18.KK | 45x70 | 416.17.68.KK | | |
| 22 | 40x92 | 416.17.19.KK | | | | |
| 25 | 45x92 | 416.17.25.KK | 40x92 | 416.17.20.KK | | |
| 30 | 45x92 | 416.17.21.KK | 50x92 | 416.17.B1.KK | | |
| 32 | 50x92 | 416.17.22.KK | 45x92 | 416.17.D5.KK | | |
| 35 | 50x92 | 416.17.57.KK | 45x117 | 416.17.64.KK | | |
| 40 | 50x92 | 416.17.58.KK | 45x117 | 416.17.27.KK | | |
| 50 | 50x117 | 416.17.28.KK | 55x92 | 416.17.F2.KK | | |
| 55 | 55x120 | 416.17.66.KK | 50x117 | 416.17.84.KK | | |
| 60 | 55x120 | 416.17.56.KK | | | | |
| 70 | 60x120 | 416.17.62.KK | | | | |



UL recognition
File E192559
370V~ / 450V~

Disponibile su richiesta
Available on request

Valori omologati
Approved range
1-70µF

Altre dimensioni a richiesta
Other sizes available upon request