





2-Wege-Montagesockel (FTH)

Typ A:



Typ B:



Artikel-Nr. natur	Artikel-Bez.	KB max.	B ϕ	M	AD ϕ	H	$L_1 \times L_2$
2-Wege-Schraubsockel für Senkkopfschraube - Typ A:							
00129	FTH-13S-N	4,8	4,3	M4	8,1	7,1	15,2x 9,7 <input type="checkbox"/>
2-Wege-Schraubsockel für Spreizniete / Flachkopfschraube - Typ B:							
09442	FTH-13S-E-N	5,0	3,7	M3	7,0	7,0	15,2x 9,7 <input type="checkbox"/>
00131	FTH-14S-N	8,0	6,5	M6	12,5	9,8	22,2x15,7 <input type="checkbox"/>
22100	FTH-14S-K-N	9,0	4,5	M4	8,0	9,6	22,0x16,0 <input type="checkbox"/>
09443	FTH-14S-E-N	9,0	5,1	M5	10,2	11,0	22,5x15,0 <input type="checkbox"/>
15278	FTH-14S-A-N	9,0	6,3	M6	10,6	9,8	23,3x16,1 <input type="checkbox"/>
09415	FTH-27-12-N	12,8	5,8	M5	11,6	12,7	25,8x19,5 <input type="checkbox"/>
2-Wege-Schraubsockel für Spreizniete - Typ B: (*)							
00128	FTH-13R-N (*)	5,0	4,3	M4	8,1	7,1	15,2x 9,7 <input type="checkbox"/>
00130	FTH-14R-N (*)	7,8	5,2	M5	9,5	9,8	22,2x15,7 <input type="checkbox"/>

(*) passende Spreiznieten ($\phi B = 4,0/5,0$ mm) finden Sie im Kapitel "Montagezubehör" / Maße in mm / VPE 100 St.

Material: PA, natur - UL-94 V-2, -40°C bis +75°C
Auf Anfrage: PA, schwarz - UL-94 V-2, -40°C bis +75°C (UV-beständig)