


EURO-STYLE TERMINAL BLOCKS

4001 /4002

8 mm (0.315 in) Spacing - 1-2 poles

[Print this page](#)



[Distributor stock check](#)

[view 3d model](#)

TECHNICAL INFORMATION

HOW TO ORDER

Description

Ceramic Terminal Block

Technical Data

(maximum load at 40°C (104°F) ambient temperature)

Center to Center Spacing: 8.0 mm (0.315 in)

Nominal Cross Section: 2.500 mm²

Wire Stripping Length: 6.5 mm

Recommended Voltage Range: 400 V

Recommended operating Current: 26 A

Wire Range: 26-10 AWG

Bill of Materials

Molding : Glazed porcelain KER 111, DIN 40685

Color : White

Upper Temperature Limit 1 : 240°C (464°F) :

Visual Description

RoHS WEEE Pb free surface compliant



Please fill in the How to Order box

- ☐ Request Sample
- Quantity
- ☐ Request Quote
- Quantity

400

Poles:

Select one

- OPTIONS:
- ☐ BS: Brass Screws
- ☐ G05: Gold Plating (5 micro inches)
- ☐ G30: Gold Plating (30 micro inches)
- ☐ S30: Silver Plating (30 micro inches)

Notes

Plated component: terminal body

ADD TO CART