

## EURO-STYLE TERMINAL BLOCKS

### 4005-A (-HDS)

Variable Spacing - 3 poles

[Print this page](#)



[Distributor stock check](#)

[view 3d model](#)

## TECHNICAL INFORMATION

## HOW TO ORDER

### Description

The Type 4005-A ceramic socket terminal was designed to connect wiring from the top and bottom when there is insufficient space along the sides of the cylindrical shape for wiring. Note that the Type 4005 does not have any mounting holes. One pole is identified with a grounding mark. Due to the exposed nature of the screws this ceramic terminal block has to be insulated from conductive surfaces.

Ceramic Terminal Block

Cylindrical

### Technical Data

(maximum load at 40°C (104°F) ambient temperature)

**Nominal Cross Section:** 2.500 mm<sup>2</sup>

**Wire Stripping Length:** 6.5 mm

**Recommended Voltage Range:** 400 V

**Recommended operating Current:** 26 A

**Wire Range:** 10 AWG

### Bill of Materials

**Molding :** Glazed porcelain KER 111, DIN 40685

**Color :** White

**Upper Temperature Limit 1 :** 200°C (392°F) :

### Visual Description

RoHS WEEE Pb free surface compliant



Please fill in the How to Order box

- ☐ Request Sample
- Quantity
- ☐ Request Quote
- Quantity

4005-A

Wire protector:

Select one

- OPTIONS:
- ☐ BS: Brass Screws
- ☐ G05: Gold Plating (5 micro inches)
- ☐ G30: Gold Plating (30 micro inches)
- ☐ S30: Silver Plating (30 micro inches)

Notes

Plated component: terminal body

ADD TO CART