

Mecal S.r.l.
 Strada per Felizzano 18
 I - 15043 Fubine (AL)
 ph. +39 0131 792792
 fax +39 0131 792733/4
 www.mecal.net



FAMP Magnum Applicator

FMP Magnum Applicator

Pneumatic end-feed



Specifications

- ID**
FMP
- DESCRIPTION**
End-feed magnum applicator
- CRIMPING HEIGHT**
135.8 mm (5.346")
- STROKE**
40/30 mm (1.575/1.18")
- TERMINAL PITCH**
not binding
- TERMINAL THICKNESS**
1.2 to 1.5 mm (0.047" to 0.059")
- WIRE SECTION**
max 25 mm² (3 AWG)
- FEEDING SYSTEM**
air pressure 5/6 bar
- WEIGHT**
7.4 Kg (16.3 lb)
- DIMENSION (mm)**
W 128 x H 145.5 x D 320
- DIMENSION (")**
W 5.04 x H 5.72 x D 12.5



Azienda con Sistema Qualità
 certificato N° 501001810

Applicator for terminals linked " end to end ", with thickness between 1.2mm and 1.5mm, wire section up to 25mm². Pneumatic " end-feed " feeding system. Exclusively fitted with a continuous regulating head having a resolution of 0.02 mm and a 2.7 mm range. Complete with a non-resettable, 7 digit cycle counter. Most of the wearing parts can be replaced without removing the applicator from the press. Can be fitted to any crimping press having a crimping height (measured from the applicator mounting plate to the press " T " coupling when at Bottom Dead Center) of 135.8mm. It is supplied with a complete technical documentation containing all the information needed to safely use and correctly maintain the equipment. Upon request, a capability study (including a picture of a sectioned crimped terminal) can be performed.

Produced under a quality Management System certified to ISO 9001 and 14001 (TÜV).

Specifications subject to change. Consult Mecal S.r.l. for latest specifications.

Mecal S.r.l.
Strada per Felizzano 18
I - 15043 Fubine (AL)
ph. +39 0131 792792
fax +39 0131 792733/4
www.mecal.net



LAMP Magnum Applicator

Magnum Applicator

Pneumatic left-side feed



Specifications

ID
LMP

DESCRIPTION
End-feed magnum applicator

CRIMPING HEIGHT
135.8 mm (5.346")

STROKE
40/30 mm (1.575/1.18")

TERMINAL PITCH
not binding

TERMINAL THICKNESS
1.2 to 1.5 mm (0.047" to 0.059")

WIRE SECTION
max 25 mm² (3 AWG)

FEEDING SYSTEM
air pressure 5/6 bar

WEIGHT
7.4 Kg (16.3 lb)

DIMENSION (mm)
W 320 x H 145.5 x D 140

DIMENSION (")
W 12.5 x H 5.72 x D 5.51



Azienda con Sistema Qualità
certificato N° 501001810



Applicator for linked terminals rolled over a reel to be unrolled "left to right", with thickness between 1.2mm and 1.5mm., wire section up to 25mm². Pneumatic "left-side feed" feeding system. Exclusively supplied with a continuous regulating head having a 0.02mm resolution and a 2.7mm range. Complete with a non-resettable, 7 digit cycle counter. All the wearing parts can be replaced without removing the applicator from the press. Can be fitted to any crimping press having a crimping height (measured from the applicator mounting plate to the press "T" coupling when at Bottom Dead Center) of 135.8mm ± 0.02mm. It is supplied with a complete technical documentation containing all the information needed to safely use and correctly maintain the equipment. Upon request, a capability study (including a picture of a sectioned crimped terminal) can be performed.

Produced under a quality Management System certified to ISO 9001 and 14001 (TUV).

Specifications subject to change. Consult Mecal S.r.l. for latest specifications.