

Amphenol LTW Innovation in Waterproof Solution



Part Number : **PWH-05BFFC-LL8001**

Pin : Copper Alloy,Gold Plated

Connector Body : Nylon+GF,UL Recognized

Temperature Range : -40°C~105°C

| Description | Details |
|---------------------|------------------------------|
| Connector | Power Connector |
| Connector Gender | Female connector |
| Mating Style | 2 point lock bayonet |
| Current Rating | 25A |
| Number of Contacts | 5 pins |
| Contact Gender | Female pin |
| Assy Style | Field Installable (Crimped) |
| Connector body type | Without strain relief |
| Back shell | Straight |
| Waterproof Rating | IP68,Mated |
| Cable OD ϕ | 13~16 |
| Patentds | UL2238,UL50E,UL6703A,EN61984 |

Mating Parts

Receptacle
 PWH-05PMMC-LC8001
 Overmolded with cable
 Field installable
 PWH-05BMMC-LL8001

Accessories

Amphenol LTW
 Innovation in Waterproof Solution

Copyright © 2011 ALTW TECHNOLOGY CO., LTD. All Rights Reserved.
 ADD:9F, No.657-12, Zhongzheng Road, Xinzhuang Dist, New Taipei City 242, Taiwan
 Tel:+886-2-2908-5626 E-mail: sales@ltw-tech.com Design by T.S.G