

Amphenol LTW Innovation in Waterproof Solution



Part Number : **12-04BMMM-SL8AXX**

Pin : Copper Alloy, Gold Plated

Connector Body : PU, UL Recognized

Temperature Range : -20°C~80°C

| Description | Details |
|---------------------|-----------------------|
| Connector | M12 A Code |
| Connector Gender | Male connector |
| Mating Style | Screw Thread |
| Current Rating | 4A |
| Number of Contacts | 4 pins |
| Contact Gender | Male pin |
| Assy Style | Overmolded with Cable |
| Connector body type | Without strain relief |
| Back shell | Straight |
| Waterproof Rating | IP68, Unmated |
| Standard Cable | UL 2464 PVC Cable |
| Cable OD ϕ | 6 |

Mating Parts

Receptacle

12-04PFFS-SF8001

12-04PFFS-SH8001

12-04PFFP-SF8001

12-04PFFR-SF8001

12-04PFFP-SF8003

12-04PFFP-SF8004

12-04PFFP-SF8005

12-04PFFS-SF8003

12-04PFFS-SF8004

12-04PFFS-SH8003

12-04PFFS-SH8004

12-04PFFR-SF7001

12S-04PFFR-SF7001

12-04PFFR-SF8003

12-04PFFS-SF8BXX

12-04PFFS-SF8CXX

12-04PFFS-SH8BXX

12-04PFFS-SH8CXX

Overmolded with cable

12S-04BFFM-SL7AXX

12S-04BFFM-SL7BXX

12-04AFFM-SL7AXX

12-04AFFM-SL7BXX

12-04AFFM-SR7AXX

12-04AFFM-SR7BXX

12-04BFFM-SL8AXX

12-04BFFM-SL8BXX
12-04BFFM-SR8AXX
12-04BFFM-SR8BXX
Field installable
12-04BFFA-SL8001
12-04BFFB-SL7001
12-04BFFB-SR7001

Accessories

CAP-WBDMMSA1

SS-040000-F00-YSBXX

SS-040400-FF0-TSAXX

SS-040400-MF0-TSAXX

Amphenol LTW
Innovation in
Waterproof Solution



Copyright © 2011 ALTW TECHNOLOGY CO., LTD. All Rights Reserved.
ADD:9F, No.657-12, Zhongzheng Road, Xinzhuang Dist, New Taipei City 242, Taiwan
Tel:+886-2-2908-5626 E-mail: sales@ltw-tech.com Design by T.S.G