

## Amphenol LTW Innovation in Waterproof Solution



**Part Number :** **12P-05PFFS-SF8001**

**Pin :** Copper Alloy,Gold Plated

**Connector Body :** Nylon+GF,UL Recognized

**Temperature Range :** -40°C~105°C

Description	Details
Connector	M12 A Code(Plastic)
Connector Gender	Female connector
Mating Style	Screw Thread
Current Rating	4A
Number of Contacts	5 pins
Contact Gender	Female pin
Assy Style	Solder
Connector body type	Front Fastened (See more details)
Back shell	Hexagonal
Waterproof Rating	IP68,Unmated
Size	PG9
流水號	001
Panel Cut $\phi$	$\phi$ 16.1X13.6
Patentds	UL1977
Panel Thickness	4

### Mating Parts

Receptacle  
 Overmolded with cable  
 12P-05BMMM-SL8AXX  
 12P-05BMMM-SL8BXX  
 12P-05BMMM-SR8AXX  
 12P-05BMMM-SR8BXX  
 Field installable  
 12P-05BMMA-SL8001  
 12P-05BMMB-SL7001  
 12P-05BMMB-SR7001

### Accessories

CAP-WBDMFSA1



Copyright © 2011 ALTW TECHNOLOGY CO., LTD. All Rights Reserved.  
 ADD:9F, No.657-12, Zhongzheng Road, Xinzhuang Dist, New Taipei City 242, Taiwan  
 Tel:+886-2-2908-5626 E-mail: sales@ltw-tech.com Design by T.S.G