

 \rightarrow

BST 302/ -322/ -323/ -324/ -326/ -327, Marking Strips for terminal strips Variable Spacing - poles Print this page



Distributor stock check

additional photos view 3d model

TECHNICAL INFORMATION

HOW TO ORDER

Description

The BST marker strips are designed for mounting beneath or above the terminal strips to provide circuit identification. They are held in place by the same fastener that secures the terminal strip to the panel or chassis. The BST Marking Strips are available in marked and blank versions. The white PVC marking strips are supplied with black hot stamped characters. Standard marking orientations are listed in the table above, special marking can be supplied on request, please contact our customer service department.

Width = BST-302 /-322 : 21 mm (0.83 in.) BST-323 : 28 mm (1.10 in.) BST-324 : 31 mm (1.22 in.) BST-326 & BST-327: 39 mm (1.54 in.)

For circuit identification

Strips mount beneath or above the terminal strips and are secured by mounting screws.

Technical Data

Center to Center Spacing:

Temperature Resistance:: approximately 80°C (176°F)

Bill of Materials

Visual Description

See additional photo for Marking

Orientation



Please fill in the How to Order box

 Request Sample
 Quantity

 Request Quote
 Quantity

BST		
Type: Poles:	Select one	OPTIONS: No option for this product
Marking orientation:	Select one	-

ADD TO CART